Flood Lighting

EasyLED EP43 Euro-Projector

IP65



Complete Lighting Services Ltd Tel: 01256 811600 Fax: 01256 811601 email: sales@completelighting.co.uk

web: www.completelighting.co.uk



EP43EQ

Housing:

Die cast aluminum housing and top frame, powdercoat finish over a chromate conversion coating, includes yoke and gear tray with wiring connector.

Lens:

Tempered clear flat glass lens or tempered clear flat prismatic glass lens

Mounting:

Mounts on included black powdercoated steel mounting yoke.

LumaFit LED:

Array Lumens: 8,936 Delivered Lumens: 8,211

CRI: 72 CCT: 5000K

Rated Life: 50,000 Hours 5-Year Warranty Aluminum Boards

Wattage:

Array: 74.8w, System: 82.2w

Driver:

Electronic Driver, 120-277V, 50/60Hz


Dimmable Driver

Listing & Ratings:

CE: Listed for wet locations. IP65

Operating Temperatures: -40°C to +40°C

EasyLED Catalog #	EP43 Eu	ro-Projector Description	
Complete Units Ordering Information Example: EP43EQF1X75U5KCBY			
EP43E	Model:	EP43E	
Q	LED Mfr:	Q=QSSI	
F	Optics:	F=Medium Flood	
1X	Number of Arrays:	1X=One	
<i>7</i> 5	Wattage:	75=75w	
U	Ballast:	U=120-277V	
5K	CCT:	5K=5000K	
С	Lens:	C=Tempered Clear Flat Glass Lens, P=Tempered Clear Flat Prismatic Glass Lens	
В	Color:	B=Black	
Y	Mounting:	Y=Yoke	



Flood Lighting



Complete Lighting Services Ltd Tel: 01256 811600 Fax: 01256 811601

email: sales@completelighting.co.uk
web: www.completelighting.co.uk

EasyLED EP43 Euro-Projector

Catalog #	Description	
EP43GLP	Tempered clear flat prismatic glass lens	



EP43GLP

