

5ft twin Willow IP65 LED Anti Corrosive

Features In Brief:

- 1. Energy saving exceeding 70%
- Even light distribution
- 3. Original Epistar chips
- Instant start, no flicking, no humming
- 5. Custom design light guide cover
- 6. High lumen output
- 7. 3 year warranty
- Emergency and dimmable options available



CLS LED Anti Corrosive fittings are designed to replace the traditional Anti corrosive fluorescent type. This 60w version offers in excess of 5,000lm. These fittings are a truly fit and forget solution with a 3 year warranty for confidence. This range also offers an emergency version, dimming and sensor options are also available on request.

| Part Number | Colour | Luminous Flux |
|------------------|--------|---------------|
| CLSHWCP230/6000k | 6000K | 5,850 lm |
| CLSHWCP230/4000K | 4000K | 5,700 lm |
| CLSHWCP230/3000K | 3000K | 4,850 lm |




5ft twin Willow IP65 LED Anti Corrosive fitting Product Features

60w Range

| Item | CLSHWCP230/6000K | CLSHWCP230/4000K | CLSHWCP230/3000K |
|-------------------------|-------------------------|-------------------------|-------------------------|
| | 5ft twin anti corrosive | 5ft twin anti corrosive | 5ft twin anti corrosive |
| Total power Consumption | 60W | 60W | 60W |
| Colour | Daylight | Cool White | Warm White |
| Colour Temperature | 6000k | 4000k | 3000k |
| Life Time | >35,000 Hour | >35,000 Hour | >35,000 Hour |
| Operating Temperature | -10°C to + 45°C | -10°C to + 45°C | -10°C to + 45°C |
| Dimensions (mm) | 1540 x 140 x 100 | 1540 x 140 x 100 | 1540 x 140 x 100 |
| Lumen | 5,850lm | 5,700lm | 4,850lm |
| Certificates | CE, RoHS,WEEE | CE, RoHS,WEEE | CE, RoHS,WEEE |
| Beam Angle | 180° | 180° | 180° |
| Power factor | >90 | >90 | >90 |
| CRI | >80 | >80 | >80 |

Light distribution diagram



Chromaticity plot

