

# LYRA II LED

Dropped modular 600 x 600mm luminaire with exceptional low glare and minimal protrusion into the lit space. Slot in side opal wings and fixed central micro prism panel allows for quick simple installation, maintenance and cleaning. Enclosed design reduces dust ingress, improving luminaire maintenance factor.



## PRODUCT SPECIFICATION & FEATURES

- LONG LIFE, ENERGY EFFICIENT LED'S
- SATIN OPAL CENTRE PANEL
- 90MM RECESSING DEPTH
- SUITABLE FOR 15 / 24MM EXPOSED TEE CEILING GRID
- CAN BE MANUFACTURED TO SUIT OTHER CEILING TYPES
- LOW GLARE LG7 COMPLIANT
- EVENLY ILLUMINATED SATIN OPTIC
- 5 YEAR WARRANTY ON TRIDONIC LED COMPONENTS
- 3922 LUMINAIRE LUMENS, 41.2W @ 45 deg, 96.8 LM / W

## CATALOGUE REFERENCE:

LYR II / LED / 66 / OP / \*

## \* CONTROL GEAR OPTIONS

- F - FIXED
- DSI - DIMMING
- DALI - DIMMING
- SWITCHDIM - DIMMING
- MS - MICROWAVE SENSOR