

# 200w Lime Linear LED

## Lowbay

### FEATURES IN BRIEF

1. Energy saving exceeding 50%
2. Uniformed light distribution.
3. Original Edison chips
4. Instant start, no flicking, no humming.
5. Philips Driver
6. 5 year warranty
7. 0-10v Dimmable as standard



CLS LED linear lowbays are designed to replace the traditional metal halide and Sodium types offering an energy saving alternative. Using the best quality materials available we achieve true lifetime claims and low lumen depreciation levels. These fittings considerably lower maintenance and energy cost and are compatible with dimming systems and motion sensors.

| PART NUMBER   | COLOUR | LUMINOUS FLUX |
|---------------|--------|---------------|
| HLLB200/6000K | 6000K  | 24,520 lm     |
| HLLB200/4000K | 4000K  | 24,360 lm     |
| HLLB200/3000K | 3000K  | 24,250 lm     |

## Lime Linear LED Highbay Product Features

| 200W RANGE            |                     |                     |                     |
|-----------------------|---------------------|---------------------|---------------------|
| ITEM                  | HLLB200/6000k       | HLLB200/4000k       | HLLB200/3000k       |
| Input Voltage         | 240v                | 240v                | 240v                |
| Power Consumption     | 150W                | 150w                | 180w                |
| Colour                | Daylight            | Cool White          | Warm White          |
| Colour Temperature    | 6000k               | 4000k               | 3000k               |
| Life Time             | >50,000 Hour        | >50,000 Hour        | >50,000 Hour        |
| Operating Temperature | -30°C to + 30°C     | -30°C to + 30°C     | -30°C to + 30°C     |
| CRI                   | 80                  | 80                  | 80                  |
| Lumen                 | 24,520lm            | 24,360lm            | 24,250lm            |
| Certificates          | CE, RoHS, FCC, WEEE | CE, RoHS, FCC, WEEE | CE, RoHS, FCC, WEEE |
| Beam Angle            | 120°                | 120°                | 120°                |
| Weight                | 5.7kg               | 5.7kg               | 5.7kg               |
| IP Rating             | IP20                | IP20                | IP20                |

### PRODUCT VIEW



### LIME LOWBAY DIMENSIONS

